


Application of cementitious grout



Clean and remove any loose particles. Make sure that the tile joints are clean and saturated and excess water is removed from the joints before grouting



Gradually add approximately 2.5 parts of powder to 1 part of clean water (measured by volume) and mix to a smooth workable stiff paste.



Keep the wet mortar idle for 3 minutes, for maturation.




Do not attempt to extend the pot life by adding more water to the mix.



Completely fill the tile joints with grout diagonally across the tile surfaces using a rubber grouting trowel or an appropriate tool



Wait till grout has started to set (30 - 45 minutes)



Remove excess grout using a wet sponge (45 - 60 minutes)



After drying clean the tiles using a dry cloth

Health & safety: Joint fillers are non- toxic. Use of gloves and goggles is recommended. Any splashes to the skin or eyes should be washed off with clean water. In the event of prolonged irritation, medical advice should be sought. Weber components are non flammable.

Disclaimer: Information on this datasheet is to be treated as guideline for usage. Users are advised to undertake a trial for product suitability prior to its full scale usage. There is no express or implied guaranty/ warranty for the results. The company is not liable for any consequential damages.

weber
Connect
18004252778
www.weber.co.in



Saint-Gobain India Pvt. Ltd. – Weber business,
5th Level, Leela Business Park,
Andheri-Kurla Road, Andheri (East),
Mumbai – 400 059, Maharashtra. India.
Email: weber-india@saint-gobain.com
Website: www.weber.co.in

cementitious tile grout



**When water
absorption can spoil it,
we guard it.**

weber
SAINT-GOBAIN

weber.color fine

Features:

- weber.color fine is a **polymer modified cementitious** tile grout used for internal application
- Enhances the decor of interiors
- It is suitable for grouting ceramic tiles, vitrified tiles, marbles, granites, mosaics, natural stone and artificial stone on walls and floors
- Recommended for use having a tile joint of 1-6mm width



Pack size: 1kg, 30kg

Consumption depends on tile size and joint width

Tile size in mm	300X300	450x450	600x600	800x800
Tile size in inches	12x12	18x18	24x24	32x32
Thickness in mm	6	7	8	9
Joint width	consumption in kg/sqm			
2 mm	0.15	0.12	0.10	0.09
3 mm	0.23	0.18	0.15	0.13
5 mm	0.36	0.30	0.25	0.21

weber.color dewdrop

Features:

- weber.color dewdrop is a **high polymer modified cementitious** water repellent tile grout used for internal application
- Prevents crack, water seepage, helps adjust the size variations and other aesthetic flaws in the tiles
- It is suitable for grouting ceramic tiles, vitrified tiles, marbles, granites, mosaics, and natural and artificial stone on walls and floors
- Especially suited for wet areas such as bathrooms, swimming pools.
- Recommended for use having a tile joint of 1-6mm width




Pack size: 1kg, 30kg

Consumption depends on tile size and joint width


Tile size in mm	300X300	450x450	600x600	800x800
Tile size in inches	12x12	18x18	24x24	32x32
Thickness in mm	6	7	8	9
Joint width	consumption in kg/sqm			
2 mm	0.15	0.12	0.10	0.09
3 mm	0.23	0.18	0.15	0.13
5 mm	0.36	0.30	0.25	0.21



White



Ivory



Floral White



Tuscan White



Beige



Desert Dune



Tropical Glory



Mushroom



Jaisalmer



Teracotta



Chocolate



Oceanic Blue



Alpine Blue



Taupe



Emerald



Grey



Misty Grey



Graphite



Jet Black